

## DEX-DMP-30

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

### Product data

#### Usage

DMP-30 is a good accelerator for curing epoxy and polyurethane systems. It is widely used in industrial coatings, casting, epoxy flooring, concrete protection and adhesives, etc.

#### Packing

- DRUM / IBC

### Technical Properties

Property	Unit	Value
Color	GARDNER	AMBER TRANSPARENT LIQUID
Purity	%	96 MIN
Amine value	MG KOH/G	580-630
Viscosity	MPA.S,25°C	160-260
Water	%	0.5 MAX
Density	25°C	0.97-0.99

### © DEXRESIN

China  
Jiangsu, Changzhou  
Tel +86 0512 63659101

[sales@dexresin.com](mailto:sales@dexresin.com)  
[info@dexresin.com](mailto:info@dexresin.com)

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.