



Data sheet Issue 11/22

# **DEX-1001**

Solid Epoxy Resin

### **Product data**

#### Decription

DEX-1001 is is a low molecular weight solid epoxy resin derived from a liquid epoxy resin and bisphenol a it can be hardening at room temperature or higher temperature

#### Packing

- 25KG/BAG

## **Technical Properties**

Property	Unit	Value
Apperance		SOLID, NO MECHANICALI MPURITIES
Epoxy t equivalent weight	G/EQ	492 -530
Softening point	°C	64-76
Volatile	%	1 MAX

## **Applications**

It can be hardening at room temperature or higher temperature, used for adhesion agent, anticorrosive coating, zinc dust ground coat, floor paint, decorated coating and varnish. It also can enhance the capability of alkyd-armine coating, to improve the levelling property of epoxy and polyester powder coating.

### © DEXRESIN

China Jiangsu, Changzhou Tel +86 0512 63659101

sales@dexresin.com info@dexresin.com

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.